



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IPW

In re Patent Application of

REID

Atty. Ref.: 620-415

Serial No. 10/567,456

Group: 2615

Filed: February 7, 2006

Examiner: Ensey

For: ELECTRO-ACOUSTIC DEVICE FOR CREATING  
PATTERNS OF PARTICULATE MATTER

\* \* \* \* \*

February 6, 2009

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

**SUBMISSION**

It is respectfully requested that this application be given the benefit of the foreign filing date under the provisions of 35 U.S.C. §119 of the following, a certified copy of which is submitted herewith with a verified English translation:

Application No.

Country of Origin

Filed

0318531.1

GB

7 August 2003

Respectfully submitted,

**NIXON & VANDERHYE P.C.**

By:

B. J. Sadoff  
Reg. No. 36,663

BJS:pp  
901 North Glebe Road, 11th Floor  
Arlington, VA 22203-1808  
Telephone: (703) 816-4000  
Facsimile: (703) 816-4100

Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents originally filed in connection with patent application GB0318531.1 filed on 7 August 2003.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed



Dated 20 January 2009



09AUG03 EB28616-18 000060  
P01/7700 0.00-0318531.1

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

MJS//NP6064828

2. Patent application number

(The Patent Office will fill in this part)

0318531.1

7 AUG 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

SONIC AGE LTD  
56 WILLOW WAY  
PONTELAND  
NEWCASTLE UPON TYNE  
NE20 9RF

Patents ADP number (if you know it)

8689382001

If the applicant is a corporate body, give the country/state of its incorporation

GB

4. Title of the invention

ELECTRO-ACOUSTIC DEVICE FOR CREATING PATTERNS OF PARTICULATE MATTER

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

MEWBURN ELLIS  
York House  
23 Kingsway  
London WC2B 6HP

Patents ADP number (if you know it)

109006

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

22

Claim(s)

4

Abstract

1

Drawing(s)

3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

2

Request for preliminary examination and search (*Patents Form 9/77*)

1

Request for substantive examination (*Patents Form 10/77*)

1

Any other documents  
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

06 AUGUST 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

MICHAEL JOHN SANDERSON 0191 232 8685

### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

ELECTRO-ACOUSTIC DEVICE FOR CREATING PATTERNS OF  
PARTICULATE MATTER

This invention relates to an electro-acoustic device  
5 for creating patterns of particulate matter each pattern  
being indicative of the harmonic structure of the  
particular audio signal fed to the device.

It is well established theory that the inherent  
10 harmonic structure of an audio signal can be rendered  
visible by exciting particulate matter to create a pattern  
associated with that signal.

For example, in 1785, E.F.P. Chadni demonstrated this  
15 modal phenomenon by exciting a brass plate carrying sand  
using a violin bow, resulting in the formation of sand  
patterns caused by the various modal flexions of the plate  
at the plate's natural frequencies.

20 In 1885, Hermann Helmholtz experimented with sand-  
strewn India-rubber membranes stretched over glass bottles  
excited by the power of voice alone, and this was repeated  
in 1904 by Margaret Watts-Hughes, the India-rubber membrane  
being stretched over a wooden vessel, vocal sounds entering  
25 a tube connected to the vessel.

Hans Jenny, a Swiss scientist, published a book entitled 'Kymatic' in 1967 in which he refers to a device which he named a 'Tonoscope' for creating vibrational patterns acoustically without any intermediate electro-acoustical unit.

To date, the value of being able to create patterns of particulate matter indicative of associated audio signals has not been fully appreciated, and it would be desirable to be able to provide an electro-acoustic device capable of creating such patterns and with a variety of practical applications.

According to the present invention there is provided an electro-acoustic device for creating patterns of particulate matter, the device comprising a housing one end of which is closed and the other end of which is open, a diaphragm extending across the housing at or adjacent the open end of the housing to define and close a hollow interior to the housing, a mass of particulate matter located on the diaphragm, and, within the hollow interior of the housing, an electro-acoustic transducer, the arrangement being such that, in use with the diaphragm extending horizontally and on activation of the transducer

by an audio signal, the acoustic output therefrom excites the diaphragm and creates a pattern in the particulate matter thereon indicative of the structure of the audio signal.

5

Such a device has a multitude of applications and the audio signal triggering the patterns can be from any one of a variety of sources. For example the device can be used to teach the fundamentals of music and musicology with the  
10 audio signal being music in any one of a number of different forms, or can be used by speech therapy practitioners as a teaching aid for stroke victims, the deaf and the partially deaf, with the audio signal being derived from the human voice. Other applications will  
15 become apparent.

In a preferred embodiment of the invention, the upper end of the housing is closed by a transparent window overlying the diaphragm and through which the patterns in  
20 the particulate matter can be viewed.

Such a window reduces the escape of sound from the housing and reduces acoustic feedback whereby a wider range of sources, including 'live' microphones, can be used to  
25 activate the transducer.

Any problems associated with acoustic feedback can be further eliminated by mounting the housing in an outer enclosure, while the volume of air between the housing and the outer enclosure may be totally or partially evacuated.

In such an embodiment, it is preferred that elasticated suspension means are provided to assist in mechanically decoupling the housing and the outer enclosure, so suspending the housing within the outer enclosure that direct conduction of acoustic energy between the housing and the outer enclosure is reduced.

The diaphragm may comprise a tensioned sheet of elastic material such as pvc extending across the housing, the tension in which sheet may be pre-set or may be adjustable.

The particulate matter is typically sized to between 250 and 1000 microns, and may be, for example, crushed quartz crystal or proprietary micro glass spheres.

The electro-acoustic transducer is conveniently a loudspeaker located coaxially within the housing with its



acoustic output directed towards the underside of the diaphragm.

In an alternative embodiment of the invention, the housing may incorporate a waveguide arranged to feed an acoustic signal from the electro-acoustic transducer to be incident upon the upper or lower surface of the diaphragm.

Such an embodiment may further comprise means for projecting the patterns in the particulate matter onto a viewing panel external of the housing.

The means for projecting the pattern may comprise a source of light within the hollow interior of the housing, a lens, preferably a flat fresnel lens, below the diaphragm, and a focusing lens above the diaphragm, the diaphragm being transparent.

In a further embodiment of the invention, the device includes a video camera located above the diaphragm and arranged to transmit signals to a remote viewing location whereby the patterns in the particulate matter can be viewed at said location.

By way of examples only, embodiments of the invention will now be described in greater detail with reference to the accompanying drawings of which:

5        Fig. 1a is a vertical section through a first device according to the invention;

         Fig. 1b is a detail of Fig. 1a to a larger scale;

         Fig. 1c is a view in the direction of arrow C in Fig. 1b (with the upper bezel removed);

10       Fig. 2 is a vertical section through a second device according to the invention, and

         Fig. 3 is a vertical section through a third device according to the invention.

15       Referring to Fig. 1 there is shown a first device according to the invention comprising a housing indicated generally at 2 which is preferably of circular transverse section and of, for example, an acrylic plastic material which may be transparent or opaque.

20

         The precise size and shape of the housing 2, its wall thickness and the material thereof are chosen to minimise acute natural resonances in the device on actuation thereof which may otherwise adversely affect the formation of

25       consistent patterns in the particulate material. Curved

housings generally perform better than angular housings in terms of natural resonances due to the manner in which wave fronts reflect off the internal surfaces of the housings.

5        The housing 2 comprises tubular member 4 the bottom end of which is closed by an acrylic disc 6 sealed in the tubular member 4 by an O-ring 8.

10        A diaphragm 10, typically of pvc sheet material 0.2mm thick is stretched across, to close, the upper end of the tubular member 4. More particularly upper and lower annular bezels 12,14 are mounted in the upper end of the tubular member 4 with an O-ring 16 reacting between the lower bezel 14 and the tubular member 4 to effect a sealing  
15 connection therebetween.

20        The edge region of the diaphragm 10 is located between the upper and lower bezels 12,14 with a plurality, typically 12, tensioning devices 18 equally spaced around the tubular member 4 reacting between the diaphragm 10 and the bezels 12,14 to enable adjustment of the tension in the diaphragm 10.

25        Each tensioning device 18 comprises a length of steel wire 20 linked to the diaphragm 10, and a winding gear 22

incorporating a tuning screw 24 rotatable to draw the wire 20 around the winding gear 22 and to tension the diaphragm 10 accordingly.

5       The material of the diaphragm 10, in particular the density, thickness and stiffness of the material of the diaphragm 10; and the overall area of the diaphragm 10 are important factors in relation to the frequency range of sounds to be displayed/studied by the device. For example,  
10 smaller, stiffer diaphragms are easier to excite into higher frequency modes of resonance than larger, more elastic diaphragms, such larger, more elastic diaphragms being easier to excite into low frequency modes of resonance.

15

      The overall tension in the diaphragm 10, together with the distribution of the tension, are fairly critical to operation of the device, effectively 'tuning' the device. Thus it is preferable to incorporate the above-described  
20 tensioning devices 18, which may be factory set at 20°C and a pressure of 1010 millibars, whereby ambient temperature and local atmospheric pressure can be accommodated by adjustment of the tensioning devices 18.

Under certain extreme circumstances, it may be necessary to perform adjustments to the device according to a specific protocol - for example exciting the diaphragm by applying a sinusoidal signal of a specific frequency to the transducer 26, the diaphragm 10 being tuned until a specific archetypal form is observed in the particulate matter.

In a simpler, more economic version of the device suitable for operation under temperature and pressure conditions within certain tolerances, the tension of the diaphragm 10 is pre-set in the factory, the diaphragm 10 being clamped between upper and lower bezels with no adjustment thereafter being possible.

15

An electro-acoustic transducer, for example a full range loudspeaker 26 is located within the housing 2 below the diaphragm 10, the loudspeaker being mounted on a baffle plate 28 to be coaxial with the tubular member 4 and the diaphragm 10 and to direct its acoustic output onto the underside of the diaphragm 10.

20

A feed cable 30 from an external source to the loudspeaker extends through an air-tight gland 32 in the tubular member 4.

25

The back pressure of the loudspeaker 26 is fully enclosed in an 'infinite baffle' arrangement so that:

- a) natural transducer resonances tend to be  
5 dampened, thus helping to flatten the transducer's overall response. This ensures that the diaphragm 10 is excited with the minimum of resonant peaks (such peaks, if existing, would cause disproportionate excitation of the diaphragm and disrupt the expected modal patterns);
- 10 b) the escape of sound from the housing is reduced.

Although the spacing between the loudspeaker 26 and the diaphragm 10 is not critical, a distance based on the phi ratio (1:1.618) generally produces optimal results -  
15 i.e. for a diaphragm diameter of 10 units, the distance between the loudspeaker and the diaphragm is set at 6.18 units.

An exception to this rule is in scientific  
20 applications where, if patterns of shorter wavelengths are being studied, better results may be achieved with shorter distances or even by direct coupling of the loudspeaker with the diaphragm.

Particulate matter 34, for example crushed quartz crystal typically sieved to between 250 and 1000 microns, or proprietary glass spheres similarly sized, is sprinkled onto the diaphragm 10. The mass of the particulate matter 5 34 is a consideration depending upon the frequencies to be studied. For example, patterns resulting from low audio frequencies (e.g. frequencies up to 500 Hz) may be formed from almost any particulate matter, whereas patterns resulting from high frequencies (in the range 500 Hz -20 10 KHz) generally form better with lower mass particulates. This is because modes of vibration at higher frequencies cause progressively less excursion of the diaphragm as the frequency increases, due to their shorter wavelength. Thus only low mass particulate matter is transported to the 15 nodal areas, and heavier particulate matter tends to remain stationery due to frictional forces. One method of countering this effect is to employ a separate high frequency transducer or tweeter arranged in an array with the main transducer. In so doing, greater sound pressure 20 levels become available at these high frequencies, thus increasing excitation/excursion of the diaphragm at high frequencies.

The volume of the particulate matter is an important 25 factor in the formation of patterns. Too great a volume

prevents their proper formation, whereas too little may provide an incomplete pattern. The optimum volume of particulate matter is a function of the diaphragm area, and 1 cubic centimetre of particulate matter for every 200 square centimetres of diaphragm area has been found to be satisfactory.

A transparent acoustic window 36 is sealingly located in the upper bezel 12 and closes the upper end of the device to retain the particulate matter 34 on the diaphragm 10 and to reduce the escape of sound from the housing 2. A cavity of typically 20mm between the upper surface of the diaphragm 10 and the underside of the window 36 is generally sufficient to allow free movement of the particulate matter 34 and to provide some reduction in sound escape. Without an acoustic window, use of a 'live' microphone as the source of sound becomes almost impossible due to acoustic feedback.

In order that patterns in the particulate matter 34 can be clearly seen, the particulate matter should have a high degree of colour contrast against that of the diaphragm. Colour dyed particulate matter can also be used - by sieving the particulate matter into grades and colour dying each grade in a given protocol of colours, the



particulate matter becomes sorted by the exciting vibrations, causing colour fringing effects within the patterns.

5        Levelling of the diaphragm 10 is important, since the particulate matter 34 will gather towards one side of the diaphragm if the diaphragm is not horizontal. A spirit level of the bullseye type is generally adequate for this purpose, either as an integral feature of the device or as  
10    an accessory.

      In use of the device, the loudspeaker 26 may be fed with a variety of pre-recorded audio signals, including voice, music and oscillator waveforms, all of which may be  
15    conveniently stored in solid state memory within an integrated or separate electronics section of the device. Alternatively, the device may be provided with sound bytes stored on Compact Disc or MiniDisk or other format of sound signal storage, which the user plays on an appropriate  
20    playback system, via a proprietary screened cable, or the sound bytes may be transmitted acoustically to the electronics section of the device and picked up via that section's internal microphone.

An external live microphone may also be employed with the device in order that voice sound patterns may be viewed, although care must be taken to ensure that the distance between the microphone and the housing 2 is carefully controlled in combination with the overall gain of the electronics section of the device. Otherwise acoustic feedback may occur.

It may be desirable initially to distribute the particulate matter evenly over the diaphragm by a deliberate noise pulse, in preparation for formation of a pattern. This could be achieved by typically a 1-second burst of pink noise, conveniently stored in solid state memory within the electronics section of the device and retrieved at the push of a button on a control panel of the electronics section. This burst of noise is fed to the transducer at a sufficient level to cause the particulate matter to randomise over the surface of the diaphragm.

In use, the described device creates patterns within the particulate matter 34 indicative of the harmonic structure of sound. The particulate matter 34 gathers in nodal areas on the tensioned diaphragm 10 which is excited into modes of acoustic vibration by incident sounds emitting from the loudspeaker 26.

When fed to the loudspeaker 26, simple sinusoidal waveforms create modal patterns of simple structure, while complex musical waveforms, which are rich in harmonics, produce complex patterns. The device generates patterns in a consistent manner provided the tuning of the diaphragm is in accordance with designed parameters.

The described device has numerous applications including:

Educational establishments, e.g. teaching the fundamentals of music and musicology;

Natural history museums, e.g. to display bird song patterns and land animal/aquatic mammal sound patterns;

15 Ancient history museums e.g. to display ancient musical instrument patterns;

Science museums e.g. helping to unravel the physical constants of the Cosmos via mathematical analysis of patterns, and displaying contemporary musical instrument patterns;

20 Entertainment in the home e.g. viewing patterns of sound bytes stored on Compact Disc, MiniDisk etc. and viewing voice sound patterns (provided some basic precautions are taken to minimise acoustic feedback).

Referring to Fig. 2, there is shown a second device according to the invention in which the device of Fig. 1 is located in an outer enclosure 38 whereby acoustic feedback is further controlled by minimising the escape of sound from the housing 2. Such an arrangement enables the use of a 'live' microphone as the source of sound in all but the most extreme circumstances.

More particularly the enclosure 38 comprises a tubular member 40 and a base disc 42 sealed in one end thereof, the upper end of the tubular member 40 being closed by a transparent window 44. The tubular member 40 and disc 42 may be an opaque acrylic material, while the window 44 may be of glass or plastic. The enclosure 38 may be lined with an acoustically absorbent material in order further to enhance the enclosure's sound attenuation properties by reducing internal standing waves and reflections.

The housing 2 is suspended in the outer enclosure 38 in such a way that direct conduction of acoustic energy between the housing 2 and the outer enclosure 38 is minimised.

More particularly silicone rubber suspension members 46 circumferentially spaced about the upper regions of the

housing 2 react between the housing 2 and the outer enclosure 38, with upper and lower sets of, typically, three foam rubber buffers 48 being circumferentially spaced about the housing 2, and an acoustic foam support cone 50  
5 being provided on the disc 6 to seat in an associated indent in the disc 42.

The annular cavity between the tubular members 4,40 is typically about 50 mm wide, while the spacing between the  
10 windows 36 and 44 is kept to a minimum to maximise vision of the diaphragm 10. This spacing between the windows 36 and 44 is not critical to the sound attenuation properties of the device, as the windows 36,44 are each of substantial thicknesses, typically 12 mm.

15

The outer enclosure 38 of the device of Fig. 2 thus acts as an acoustic screen whereby, when the loudspeaker 26 is fed with live microphone signals, acoustic feedback is much reduced compared with the device of Fig. 1. Voice  
20 sound patterns are thus easily formed without the necessity to take particular care over the proximity of microphone and transducer.

Applications for the device of Fig. 2 include:

Speech therapy practitioners, for example as a teaching aid for stroke victims, the deaf and partially deaf; patients are able to 'see' the sounds they make with almost no interference from acoustic feedback;

5       Vocal coaching, either self taught or teacher taught, where it is desirable for a vocalist to perfect, for example, vowel sound annunciation;

          Overtoning practitioners, i.e. the art of creating vocal harmonics; the device of Fig. 2 permits the creation  
10   and study of such harmonics in a visual form.

          If the volume of air between the housing 2 and the outer enclosure 38 of the device of Fig. 2 is partially or totally evacuated, the attenuating properties of the outer  
15   enclosure 38 are further increased whereby voice sound patterns can be created from whispers or very quiet sounds.

          Even partial evacuation has a significant effect in reducing sound leakage, the higher the evacuation the  
20   greater become the attenuation properties of the enclosure 38.

          For any given device, there will be an optimum value to the evacuation dependent upon the precise properties of

the materials employed and the constructional method adopted in the manufacture of the device.

Fig. 3 illustrates a modified device which may embody  
5 the device of either Fig. 1 or Fig. 2, and which enables the patterns of particulate matter on the diaphragm 10 to be projected onto the ceiling, a wall or a dedicated screen, thus rendering the patterns visible without direct  
ocular vision of the diaphragm 10 and enabling viewing of  
10 the patterns by large numbers of people.

Referring to Fig. 3, in which components equivalent to those of Figs. 1 and 2 are similarly referenced, the housing 2 and the outer enclosure 38 are generally bowl  
15 shaped with the tubular members 4, 40 defining a waveguide 52 feeding to the upper surface of the diaphragm 10, which is transparent. The loudspeaker 26 feeds downwardly to propagate sound through the waveguide 52 as indicated by the arrows S, around the upper and lower bezels to be  
20 focused onto the diaphragm 10.

A light source 54 is located within the lower regions of the housing 2 above the loudspeaker 26, and a flat fresnel lens 56 is positioned under the diaphragm 10.  
25 There is a spacing of typically 10 to 20 mm between the

lens 56 and the diaphragm 10 to prevent contact between the diaphragm 10 and the lens 56 on actuation of the device.

A focusing lens 58 is arranged above the diaphragm 10,  
5 typically carried by three curved spaced support members 60  
formed by extensions of the tubular member 40.

Thus, on actuation of the device to create patterns in  
the particulate matter 34, light from the source 54 passes  
10 through the lens 56, and through the diaphragm 10 to be  
focused by the lens 58. The image may be incident on an  
optional/removable/adjustable mirror (not shown) and  
projected onto the wall or a dedicated screen.  
Alternatively, without the mirror, the patterns can be  
15 projected onto the ceiling.

The interior of the housing 2 may be ventilated by  
providing a pair of horizontal metal tunnels 62 one to each  
side of the light source 54 each passing through the  
20 waveguide 52 which is suitably protected with heat  
insulation sleeves to ensure that the temperature of the  
metal does not distort the material of the tubular members  
4,40. One end of one tunnel 62 acts as an air intake, and  
a fan/air filter combination 64 feeds air past the light  
25 source 54 and out through the other tunnel 62.



In an alternative embodiment of the invention for enabling viewing of the patterns remotely and by a large number of people, a video camera is arranged above the diaphragm 10 of a device according to Figs. 1 and 2, and the signal from the camera is either fed via a closed circuit to a proprietary monitor, projector or other display device, or is transmitted via conventional television.

10

Thus there is provided a device capable of creating a variety of patterns in particulate material in accordance with audio signals fed to an electro-acoustic component within the device and whereby the patterns are indicative of the harmonic structure of the signal in question.

15

In a further alternative embodiment of the invention, video or cinematograph moving images of modal patterns may be viewed. By sampling a recorded sound track, typically every  $1/25$  second, then time stretching the samples to, say, 5 seconds, the modal patterns representing such samples may be created, employing any embodiment of the invention, Figures 1,2 or 3, and video recorded or cinematographically filmed, sequentially frame by frame. Such a procedure creates a moving pattern for the eye when

25

replayed at not less than 25 frames per second and when  
viewed in synchronism with the recorded sounds, enhances  
the pleasure of listening, the visual element being  
indicative of the harmonic structure of the recorded  
5 sounds.

In a more advanced embodiment of the invention,  
computer simulated versions of the modal patterns, derived  
by employing embodiments of the invention, Figures 1, 2 or  
10 3, can be viewed in real time on, for example, a cathode  
ray tube, computer monitor, plasma monitor, video projector  
or hand-held display device. Sound from a live or recorded  
source is converted by a microphone into a representative-  
electrical audio signal. The signal is fed to an analogue-  
15 to-digital converter, whereupon it is processed by a  
computer at a sampling rate of, typically, not less than 25  
times per second. The wave form of the sound sample is  
compared with waveforms of all sound samples stored in the  
computer's memory and the nearest match is identified.  
20 This match triggers release from computer memory of the  
digitised image of the modal pattern associated with that  
stored sound sample. Thus, a moving set of patterns is  
seen by the viewer in synchronism with the recorded or live  
sound source.

CLAIMS

1. An electro-acoustic device for creating patterns of particulate matter, the device comprising a housing one  
5 end of which is closed and the other end of which is open, a diaphragm extending across the housing at or adjacent the open end of the housing to define and close a hollow interior to the housing, a mass of particulate matter located on the diaphragm, and, within the hollow interior  
10 of the housing, an electro-acoustic transducer, the arrangement being such that, in use with the diaphragm extending horizontally and on activation of the transducer by an audio signal, the acoustic output therefrom excites the diaphragm and creates a pattern in the particulate  
15 matter thereon indicative of the audio signal.

2. A device as claimed in claim 1 in which the upper end of the housing is closed by a transparent window overlying the diaphragm and through which the patterns in the particulate matter can be viewed.

20 3. A device as claimed in claim 2 in which the housing is mounted in an outer enclosure.

4. A device as claimed in claim 3 in which the volume of air between the housing and the outer enclosure is totally or partially evacuated.

5. A device as claimed in claim 4 in which elasticated suspension means react between the housing and the outer enclosure to suspend the housing within the outer enclosure.

5 6. A device as claimed in any one of claims 1 to 5 in which the diaphragm comprises a tensioned sheet of elastic material extending across the housing.

7. A device as claimed in claim 6 in which the tension in the sheet is adjustable.

10 8. A device as claimed in any one of claims 1 to 7 in which the particulate matter is sized to between 250 and 1000 microns.

9. A device as claimed in claim 8 in which the particulate matter is crushed quartz crystal.

15 10. A device as claimed in any one of claims 1 to 9 in which the electro-acoustic transducer is a loudspeaker located coaxially within the housing with its acoustic output directed towards the underside of the diaphragm.

11. A device as claimed in any one of claims 1 to 9  
20 in which the housing incorporates a waveguide arranged to allow the acoustic output from the electro-acoustic transducer to be incident upon the upper or lower surface of the diaphragm.

12. A device as claimed in claim 11 and further  
25 comprising means for projecting the patterns in the

particulate matter onto a viewing panel external of the housing.

13. A device as claimed in claim 12 in which the means for projecting the pattern comprise a source of light  
5 within the hollow interior of the housing, a lens below the diaphragm, and a focusing lens above the diaphragm, the diaphragm being transparent.

14. A device as claimed in any one of claims 1 to 10 and including a video camera located above the diaphragm  
10 and arranged to transmit signals to a remote viewing location whereby the patterns in the particulate matter can be viewed at said location.

15. A device as claimed in any one of claims 1 to 14 and including means whereby moving images of modal patterns, representative of a recorded sound track, may be viewed in synchronism with the sound track.

16. A device as claimed in any one of claims 1 to 14 and including means whereby moving images of computer-simulated modal patterns, representative of a recorded  
20 sound track, may be viewed in synchronism with the sound track.

17. A device as claimed in any one of claims 1 to 14 and including means whereby moving images of computer-simulated modal patterns, representative of a live sound

performance, may be viewed in real time, during progress of the performance.

18. An electro-acoustic device for creating patterns of particulate matter substantially as described with  
5 reference to and as illustrated by the accompanying drawings.


ABSTRACTELECTRO-ACOUSTIC DEVICE FOR CREATING PATTERNS OF  
PARTICULATE MATTER

5

An electro-acoustic device for creating patterns of particulate matter comprises a housing (2) one end of which is closed and the other end of which is open, a diaphragm (10) extending across the housing (2) at or adjacent the open end of the housing to define and close a hollow interior to the housing, a mass of particulate matter (34) located on the diaphragm (10), and, within the hollow interior of the housing (2), an electro-acoustic transducer (26), the arrangement being such that, in use with the diaphragm (10) extending horizontally and on activation of the transducer (26) by an audio signal, the acoustic output therefrom excites the diaphragm (10) and creates a pattern in the particulate matter (34) thereon representative of the audio signal.

20


FIG. 1a





YIMA SCOPE - VERSIONS 2 & 3 1:25

FIG. 2






FIG. 3